

MMU-AP_4HP1 4-WAY CASSETTE



4-way cassette is designed to provide uniform air distribution and total user comfort making this unit the ideal solution for small commercial applications.

Comfort

- Two louver shape option: straight flow louver and wide flow louver; optimum air distribution.
- Possible to set three different and swing modes. Providing individual control to maximise end user comfort.
- Wide air flow in all directions.
- Optimal air diffusion up to 4.6m ceiling height!

Reliability

- Self-cleaning function and Ag-ion tip for anti-mould in drain cap.
- Built-in high-lift drain pump.

Easy to install

- Compact chassis with only 256mm height (up to size 30).
- Lightweight unit, for easy and quick installation.

CAPACITY



2.8kW > 18kW

SOUND PRESSURE LEVEL



27dB(A)

OUTDOOR UNITS



Side Blow & MiNi SMMS-e



SMMS-e



SHRM-e

LOCAL CONTROLS



RBC-AX32U(W)-E
TCB-AX32E2



RBC-AMS55E-ES(EN)
RBC-AMS41E
RBC-AMT32E
RBC-AS41E

4-WAY CASSETTE Performances

Indoor unit	MMU-	AP0094HP1-E/TR	AP0124HP1-E/TR	AP0154HP1-E/TR	AP0184HP1-E/TR	AP0244HP1-E/TR	AP0274HP1-E/TR	AP0304HP1-E/TR	AP0364HP1-E/TR	AP0484HP1-E/TR	AP0564HP1-E/TR
Cooling capacity	kW	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	16.0
Heating capacity	kW	3.2	4.0	5.0	6.3	8.0	9.0	10.0	12.5	16.0	18.0
Power consumption	kW	0.021	0.021	0.023	0.026	0.036	0.036	0.043	0.088	0.112	0.112
Running current	A	0.23	0.23	0.27	0.29	0.38	0.38	0.43	0.73	0.88	0.88
Starting current	A	0.30	0.30	0.33	0.36	0.42	0.42	0.59	0.87	1.23	1.26

4-WAY CASSETTE Physical data

Indoor unit	MMU-	AP0094HP1-E/TR	AP0124HP1-E/TR	AP0154HP1-E/TR	AP0184HP1-E/TR	AP0244HP1-E/TR	AP0274HP1-E/TR	AP0304HP1-E/TR	AP0364HP1-E/TR	AP0484HP1-E/TR	AP0564HP1-E/TR
Air flow (h/m/l)	m ³ /h	800/730/680	800/730/680	930/830/790	1050/920/800	1290/920/800	1290/920/800	1320/1100/850	1970/1430/1070	2130/1430/1130	2130/1520/1230
Air flow (h/m/l)	l/s	222/203/189	222/203/189	258/231/219	292/256/222	358/256/222	358/256/222	367/306/236	547/397/297	592/397/314	592/422/342
Sound pressure level (h/m/l)	dB(A)	30/29/27	30/29/27	31/29/27	32/29/27	35/31/28	35/31/28	38/33/30	43/38/32	46/38/33	46/40/33
Dimensions (HxWxD)	mm	256x840x840	256x840x840	256x840x840	256x840x840	256x840x840	256x840x840	256x840x840	319x840x840	319x840x840	319x840x840
Weight	kg	20	20	20	20	20	20	20	25	25	25
Panel dimensions (HxWxD)	mm	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950	30x950x950
Panel weight	kg	4	4	4	4	4	4	4	4	4	4
Connecting pipe, gas		3/8"	3/8"	1/2"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
Connecting pipe, liquid		1/4"	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Drain port diameter	mm	25	25	25	25	25	25	25	25	25	25
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50