

MMF-AP_H1 FLOOR STANDING



This system is particularly suitable to air condition large rooms like shops or showrooms or with low ceilings like restaurants or lofts.

Optimized air flow

- The unit has been designed to have particularly high air flow rates, which correspond into superior air throw values.
- The wide and automatic vertical and horizontal air distribution angles, allow the air flow distribution to reach all areas, even when installed into large rooms.
- High air flows: from 180 l/s to 600 l/s (660 m³/h to 2160 m³/h).
- Wide air distribution angle: up to 150°.

Wide range

- Large capacity range: cooling capacities from 4.5 kW to 16 kW and heating capacities from 5 kW to 18 kW.

Installation everywhere

- The unit can be installed in the corner of the room, in this case the automatic swing angle can be fixed to deliver the air only where it is needed.
- Very small footprint: 0.128 m² up to 8 kW and 0.243 m² up to 16 kW.

CAPACITY



4.5kW > 18kW

SOUND PRESSURE LEVEL



37dB(A)

OUTDOOR UNITS



Side Blow & MINI SMMS-e



SMMS-e



SHRM-e

LOCAL CONTROLS



TCB-AX32E2



RBC-AMS55E-ES(EN)
RBC-AMS41E
RBC-AMT32E
RBC-AS41E

FLOOR STANDING Performances

Indoor unit	MMF-	AP0156H1-E/TR	AP0186H1-E/TR	AP0246H1-E/TR	AP0276H1-E/TR	AP0366H1-E/TR	AP0486H1-E/TR	AP0566H1-E/TR
Cooling capacity	kW	4.5	5.6	7.1	8.0	11.2	14.0	16.0
Heating capacity	kW	5.0	6.3	8.0	9.0	12.5	16.0	18.0
Power consumption	kW	0.055	0.055	0.089	0.089	0.135	0.160	0.160
Running current	A	0.38	0.38	0.60	0.60	0.90	1.10	1.10
Starting current	A	0.53	0.53	0.84	0.84	1.26	1.54	1.54

FLOOR STANDING Physical data

Indoor unit	MMF-	AP0156H1-E/TR	AP0186H1-E/TR	AP0246H1-E/TR	AP0276H1-E/TR	AP0366H1-E/TR	AP0486H1-E/TR	AP0566H1-E/TR
Air flow (h/l)	m ³ /h	900/660	900/660	1200/840	1200/840	1920/1380	2160/1560	2160/1560
Air flow (h/l)	l/s	250/183	250/183	333/233	333/233	533/383	600/433	600/433
Sound pressure level (h/l)	dB(A)	46/37	46/37	49/39	49/39	51/41	54/44	54/44
Dimensions (HxWxD)	mm	1750x600x210	1750x600x210	1750x600x210	1750x600x210	1750x600x390	1750x600x390	1750x600x390
Weight	kg	46	46	47	47	62	62	62
Connecting pipe, gas	in	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Connecting pipe, liquid	in	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"
Drain port diameter	mm	20	20	20	20	20	20	20
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50