

MMK-AP_HP
HIGH-WALL



Particularly compact, this high-wall is perfect for limited spaces, such as offices or small shops.

Compact and design

- The unit is compact and lightweight, it is perfect for installation above the doors or in narrow corridors.
- New appearance, simple, elegant with nice led display.

Healthy

- Special fin coating for Healthy & Fresh air

Easy to use

- Remote controller for easy access to the preferred setting.
- Filters for dust collection can be easily removed by lifting the front panel and can be cleaned easily washing them under running water.

CAPACITY



1.7kW > 7.1kW

SOUND PRESSURE LEVEL



25dB(A)

OUTDOOR UNITS



Side Blow & Mini SMMS-e



SMMS-e



SHRM-e

LOCAL CONTROLS



IR control (included)



RBC-AMS55E-ES(EN)
RBC-AMS41E
RBC-AMT32E
RBC-AS41E

COMPACT HIGH-WALL Performances

Indoor unit	MMK-	AP0057HP-E/TR	AP0077HP-E/TR	AP0097HP-E/TR	AP0127HP-E/TR	AP0157HP-E/TR	AP0187HP-E/TR	AP0247HP-E/TR
Cooling capacity	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power consumption	kW	0.013	0.015	0.016	0.017	0.028	0.032	0.050
Running current	A	0.14	0.15	0.16	0.17	0.25	0.03	0.40
Starting current	A	0.19	0.20	0.21	0.22	0.35	0.38	0.50

COMPACT HIGH-WALL Physical data

Indoor unit	MMK-	AP0057HP-E/TR	AP0077HP-E/TR	AP0097HP-E/TR	AP0127HP-E/TR	AP0157HP-E/TR	AP0187HP-E/TR	AP0247HP-E/TR
Air Flow (h/l)	m ³ /h	455/270	480/270	510/270	540/270	840/550	900/550	1200/600
Air Flow (h/l)	l/s	126/75	133/75	141/75	150/100	233/153	250/153	333/167
Sound pressure level (h/l)	dB(A)	33/25	35/25	36/25	37/25	40/38/36/34/32	41/39/37/35/32	45/42/39/36/33
Dimensions (HxWxD)	mm	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230	320 x 1050 x 250	320 x 1050 x 250	320 x 1050 x 250
Weight	kg	11	11	11	11	16	16	16
Connecting pipe. gas		3/8"	3/8"	3/8"	3/8"	1/2"	1/2"	5/8"
Connecting pipe. liquid		1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	3/8"
Drain port diameter	mm	16	16	16	16	16	16	16
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50