

- Equipped with draught prevention and clean ceiling functions this unit delivers the required amount of air without disturbing the users
- Access to the corner pockets for practical installation, maintenance and precise panel adjustment
- Built-in water condensate discharge pump
- Auxiliary fresh air make-up intake hole for constant supply



## VRF Indoor Unit Compact 4-Way Cassette

CODE		15	20	25	32	40	50
INDOOR UNIT	MMU-	AP0056MH-E	AP0074MH-E	AP0094MH-E	AP0124MH-E	AP0154MH-E	AP0184MH-E
CAPACITY CODE	hp	0.6	0.8	1.0	1.25	1.7	2.0
Cooling Capacity	kW	1.7	2.2	2.8	3.6	4.5	5.6
Heating Capacity	kW	1.9	2.5	3.2	4.0	5.0	6.3
UK Total Cooling/Sensible Cooling Capacity	kW	1.5/1.2	2.0/1.6	2.5/1.9	3.3/2.4	4.1/2.9	5.1/3.4
UK Heating Capacity	kW	1.3	1.7	2.2	2.7	3.4	4.3
Power Consumption	kW	0.034		0.036	0.038	0.041	0.052
Running Current	A	0.28		0.30	0.31	0.34	0.42
Starting Current	A	0.49		0.52	0.54	0.59	0.73
Motor Output	W	60					
Standard Air Flow H/M/L	l/s	135/128/105	153/128/105	158/130/105	165/140/112	183/153/130	212/178/145
Standard Air Flow H/M/L	m <sup>3</sup> /min	8.1/7.7/6.3	9.2/7.7/6.3	9.5/7.8/6.3	9.9/8.4/6.7	11.0/9.2/7.8	12.7/10.7/8.7
Standard Air Flow H/M/L	m <sup>3</sup> /h	486/462/378	552/462/378	570/468/378	594/504/402	660/552/468	762/642/522
Sound Pressure Level H/M/L	dB(A)	35/32/28	36/32/28	37/33/28	37/33/29	40/35/30	44/39/34
Sound Power Level H/M/L	dB(A)	50/47/43	51/47/43	52/48/43	52/48/44	55/50/45	59/54/49
Main Unit Height/Width/Depth	mm	268/575/575					
Ceiling Panel Height/Width/Depth	mm	27/700/700					
Main Unit Total Weight	kg	17					
Ceiling Panel Total Weight/Type	kg	3/RBC-UM11PG(W)-E					
Gas Side	mm - "	9.5 - 3/8			12.7 - 1/2		
Liquid Side	mm - "	6.4 - 1/4					
Drain Port (Inner/Outer)	mm	25/32					
Power supply		1 phase 230 V 50 Hz					
Suggested Fused Spur Supply	A	3			5		

### ACCESSORIES

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully programmable 7-day timer
RBC-AMS54E-ES	Lite-Vision Plus Remote Controller	Includes timer and backlight display as well as power save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and base use applications (no service function available)
RBC-SMCN61	ON/OFF And Locking Lead	Lead to remotely switch a unit ON/OFF and to lock this function
RBC-SMTI	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller