E-System One



The stylish E-System One comes with a brilliant white fascia and a host of high-end features, including the energy saving 'Auto' function.

- / **XtraTech**™ stainless steel heat exchanger
- / 'Auto' function technology
- / Comfort function
- / High efficiency pump
- / 1:7 modulation
- / Quiet operation starting at 49dB
- / Lightweight unit starting at 29kg
- / 5 year warranty
- / 'A' energy rating rated for optimum efficiency
- / Large backlit display
- / Includes LPG conversion kit
- / Ariston NET compatible

ENERGY RATING

A

*Up To 5 YEARS WARRANTY

kiwa approved product

UK WATER SUPPLY REGULATIONS

XtraTech™
stainless-steel heat exchanger

PERFORMANCE CERTIFIED BY TÜV RHEINLAND GROUP


TÜVRheinland CERTIFIED

www.tuv.com
ID 0000056520

ARISTON NET COMPATIBLE | VOICE CONTROL | SUPER SILENT | EASY TO USE | ITALIAN DESIGN | SYSTEM MANAGEMENT | AUTO FUNCTION | EASY INSTALLATION | EASY MAINTENANCE



*Warranty Ts & Cs apply




*Distance from back of boiler to front of clock

KEY


A \ Central heating flow
B \ Domestic hot water outlet
C \ Gas inlet
D \ Domestic hot water inlet
E \ Central heating return

Coaxial flue




Maximum smoke / air development:
Ø60/100: till a 8 m (24 kW) - 7 m (30 kW) - 7 m (35 kW)
Ø80/125: till a 33 m (24 kW) - 24 m (30 kW) - 27 m (35 kW)

Twin flue configurations also possible



Hydraulic scheme



Please see installation manual for full details

TECHNICAL DATA		24	30
Efficiency			
Energy rating - heating/DHW	Rating	A	A
Energy rating data - seasonal space heating efficiency	%	93	94
Energy rating data - water heating efficiency	%	-	-
Energy rating data - noise level	dB	51	49
Energy rating data - tapping profile	-	-	-
SEDBUK rating	Band	A	A
SAP efficiency 2005	%	90.1	90.3
SAP efficiency 2009/2012	%	89.5	89.5
Power & Performance			
DHW flow rate ΔT @ 35°C	l/min	-	-
Heat output max (CH)	kW	22	28
Heat output max (DHW)	kW	-	-
Min/Max heating temperature (high temp. range)	°C	35/82	35/82
Min/Max heating temperature (low temp. range)	°C	20/45	20/45
DHW temperature min/max	°C	-	-
Characteristics			
Minimum ambient temperature	°C	5	5
DHW minimum flow rate	l/min	-	-
DHW pressure - min/max	bar	-	-
Built-in expansion vessel capacity	l	8	8
Servicing clearances - top/front/bottom	mm	300/450/250	300/450/250
Servicing clearances - left/right	mm	5/5	5/5
Weight	kg	29.3	31.9
NOx	mg/kWh	53	51
Electrical Data			
Electrical supply	V/Hz	230/50	230/50
Protection grade of electrical system	IP	X5D	X5D
Product Codes		3301056	3301057

Home gets smarter, life gets simpler

Enjoy Ariston NET connectivity

Comfort at your fingertips with the Ariston NET app

Download on the App Store
GET IT ON Google Play

